

2SJJ0068-0003 Breathing Set Pneumatic



Pneumatic Driven 8-inch Duct/Fuel Ventilation System. A highly adaptive and portable system to ventilate one or multiple Aircraft Fuel Tanks at once. All equipment stores within a tough, reusable container. Provides a smaller footprint for Mobility/Deployment conditions. Achieves an unparalleled level of safety and efficiency. Operates in a wide range of set up configurations applied to the JSF aircraft. Driven with either portable or stationery compressed air supply. Proven to drastically reduce the time required to render fuel tank(s) safe for inspection or repair.



SYSTEM CONTENTS

- Pneumatic Driven Air Mover **APV-2**
- 4 ea - 8 inch Dia. X 15 ft. Conductive Ducting, **NFRA-8X**
- 4 ea - 4 inch Dia. X 15 ft. Conductive Ducting, **NFRA-4X**
- Duct Sleeve Kit
- Multiple Port Air Duct Adapter
- Inlet Compressed Air Hose Assembly
- Intake Air Filter Adapter
- Reusable Storage Container



SPECIFICATIONS

Classification:	Pneumatic Driven Air Mover System with Ducting
Compressed Air Supply Requirements:	Pressure: 80 psi (5.5 bar)
Air Filtration:	Inlet
Ventilator Air Flow Displacement:	1500 cfm (2549 m ³ /hr)
Max. Ducting Size:	8 inch Diameter Conductive

PART # DESCRIPTION

2SJJ0068-0003	Rhine Air Mobile Aircraft Fuel Tank Ventilating System, JSF
---------------	---

Berry Compliant and Made In U.S.A.